DERWENT-

1982-05623J

ACC-NO:

DERWENT-

198249

WEEK:

COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE:

Reinforced composite plastic board mfr. - by laminating polyvinyl fluoride resin sheet coated with <u>adhesive</u> to GFR

unsatd. polyester resin sheet

INVENTOR: NITO,

PRIORITY-DATA: 1981JP-0061798 (April 23, 1981)

PATENT-FAMILY:

PUB-NO		PUB-DATE			LANGUAGE	PAGES	MAIN-IPC
JP	57176160	A October	29,	1982	N/A	009	N/A
JP	86034390	B August	7, 1	986	N/A	000	N/A

INT-CL (IPC): B32B027/36

ABSTRACTED-PUB-NO: JP 57176160A

BASIC-ABSTRACT:

A surface of PVF resin sheet is coated with an <u>adhesive</u> compsn. contg. at least one resin selected from unsatd. polyester resin of bisphenol type, vinyl ester resin or oligoacrylate ester. After precuring the <u>adhesive</u> compsn., the PVF resin sheet is laminated with a <u>glass</u> fibre reinforced unsatd. polyester resin sheet so that the latter resin sheet is contacted directly with the <u>adhesive</u> layer on the PVF resin sheet and the laminateis heat treated to provide a reinforced composite board. Alternatively, the <u>adhesive</u> layer on the PVF sheet is coated with a compsn. comprising unsatd. polyester resin and <u>glass</u> fibre to be hardened afterwards.

The process provides a reinforced composite plastic board having high adhesion of the PVF resin film and $\overline{\text{FRP}}$ and having high transparency, resistance against yellowing.

Basic Abstract Text - ABTX (1):

A surface of PVF resin sheet is coated with an <u>adhesive</u> compsn. contg. at least one resin selected from unsatd. polyester resin of bisphenol type, vinyl ester resin or oligoacrylate ester. After pre-

curing the <u>adhesive</u> compsn., the PVF resin sheet is laminated with a <u>glass</u> fibre reinforced unsatd. polyester resin sheet so that the latter resin sheet is contacted directly with the <u>adhesive</u> layer on the PVF resin sheet and the laminateis heat treated to provide a reinforced composite board. Alternatively, the <u>adhesive</u> layer on the PVF sheet is coated with a compsn. comprising unsatd. polyester resin and glass fibre to be hardened afterwards.

Basic Abstract Text - ABTX (2):

The process provides a reinforced composite plastic board having high adhesion of the PVF resin film and \underline{FRP} and having high transparency, resistance against yellowing.

Title - TIX (1):

Reinforced composite plastic board mfr. - by laminating polyvinyl fluoride resin sheet coated with <u>adhesive</u> to GFR unsatd. polyester resin sheet

Standard Title Terms - TTX (1):

REINFORCED COMPOSITE PLASTIC BOARD MANUFACTURE <u>LAMINATE</u> POLYVINYL FLUORIDE RESIN SHEET COATING <u>ADHESIVE</u> GFR UNSATURATED POLYESTER RESIN SHEET

Additional Indexing Term - TTAI (1):

GLASS FIBRE REINFORCED FRP